

Teak Oil

Boatcare

Penetrating oil for protection of hardwood. Professional wipe down solvent designed to remove



PRODUCT DESCRIPTION

Teak Oil is a special penetrating oil for the protection of teak decks and teak interiors. It produces a protective and easy-clean surface.

- * Traditional Scandinavian formula, containing linseed and tung oils, for ultimate protection
- * For use on any interior or exterior hardwood
- * Produces attractive sheen finish
- * Penetrates even moist wood
- * Contains an anti-rust inhibitor for protection of metal surfaces

PRODUCT INFORMATION

Colour	YMB846
Finish	Not Applicable
Specific Gravity	0.8
Volume Solids	33%
Typical Shelf Life	2 yrs
VOC (As Supplied)	552 g/lt
Unit Size	500 ml, 4 lt - Not all pack sizes are available in all countries

DRYING/OVERCOATING INFORMATION

Drying

Overcoating

Substrate Temperature

	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
Overcoated By	Min	Max	Min	Max	Min	Max	Min	Max

APPLICATION AND USE

Preparation	Ensure bare wood is clean and dry. Clean wood with Teak Restorer if required.
Method	Apply 1-2 coats of Teak Oil with a cloth or brush. Let the oil dry before touching. Repeat during the season if required. Remove teak oil from sealant as it could soften the sealant when left on for extended periods of time.
Hints	Product temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Ambient temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Substrate temperature should be minimum 5°C/41°F and maximum 35°C/95°F.
Compatibility/Substrates	Suitable for use on interior or exterior hardwood.
Application Methods	Brush, Cloth

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Storage	GENERAL: Exposure to air and extremes of temperature should be avoided. For the full shelf life of Teak Oil to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight. TRANSPORTATION: Teak Oil should be kept in securely closed containers during transport and storage.
Safety	GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line. DISPOSAL: Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Remainders of this product cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.

IMPORTANT NOTES

The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

Please refer to your local representative or visit www.yacht-paint.com for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2022.