

Boat Shampoo

Boatcare

Concentrated Cleaner



PRODUCT DESCRIPTION

Boat Shampoo is a universal cleaner suitable for fibreglass, wood, metals and painted surfaces. It does not remove wax and can be used regularly without affecting your wax protection.

- * Can be used with salt water - convenient to use anywhere
- * Does not remove wax - can be used regularly without affecting your wax protection
- * Leaves surfaces shiny and water repellent

PRODUCT INFORMATION

Colour	YMB821
Specific Gravity	0.99
Volume Solids	15%
Mix Ratio	Light cleaning - 4 black caps to 4 litres water. Heavier cleaning - 8 black caps to 4 litres water.
Typical Shelf Life	2 yrs
VOC (As Supplied)	0 g/lit
Unit Size	500 ml

DRYING/OVERCOATING INFORMATION

Drying

Overcoating

Substrate Temperature

Overcoated By	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
	Min	Max	Min	Max	Min	Max	Min	Max

APPLICATION AND USE

Preparation	Rinse with fresh or salt water to remove loose dirt.
Method	Choose appropriate mixing ratio. Add the required number of capfuls of Boat Shampoo to fresh or salt water. Wash surface with a cloth or sponge. Wash surface section-by-section starting at the highest point first, until all dirt is removed. Dry the surface with a clean cloth for best results.
Hints	Mixing Shake well before use.
Some Important Points	Product temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Substrate temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Ambient temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Keep from freezing.
Compatibility/Substrates	Suitable for fibreglass, wood and painted surfaces.
Application Methods	Brush/Cloth/Sponge.

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Storage	GENERAL INFORMATION: Exposure to air and extremes of temperature should be avoided. For the full shelf life of Boat Shampoo to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight. TRANSPORTATION: Boat Shampoo should be kept in securely closed containers during transport and storage.
Safety	GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line. DISPOSAL: Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Remainders of Boat Shampoo cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.

IMPORTANT NOTES

The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal

Please refer to your local representative or visit <http://www.yachtpaint.com> for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2014.

Boat Shampoo

Boatcare

Concentrated Cleaner



injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

Please refer to your local representative or visit <http://www.yachtpaint.com> for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2014.

Ref:3573 Boat Shampoo Issue Date:15/12/2014