

PRODUCT DESCRIPTION

Marine Wax gives lasting protection without abrasives or silicone. Easy to work with and an ideal product for larger surfaces. This product offers a hard, long-lasting, full gloss surface and gives protection against saltwater and sunlight. For manual and machine use (800-1000 rpm).

- * Non abrasive
- * Does not leave a patchy surface
- * Also suitable for use on the car, caravan or garden furniture

PRODUCT INFORMATION

Colour	YMB834
Specific Gravity	0.95
Volume Solids	5%
VOC (As Supplied)	143 g/lt
Unit Size	500 ml

DRYING/OVERCOATING INFORMATION

Drying

Overcoating

Substrate Temperature

Overcoated By	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
	Min	Max	Min	Max	Min	Max	Min	Max

APPLICATION AND USE

Preparation	Clean surface with Super Cleaner and fresh water. Allow to dry. To achieve the best results, pretreat the surface with Marine Polish. For badly deteriorated surfaces use Liquid Rubbing first.
Method	Apply a thin layer of Marine Wax with a clean dry cloth. Allow to dry. Polish using a cloth or machine until desired gloss level is achieved, changing cloth frequently.
Hints	Mixing - Shake well before use.
Some Important Points	Product temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Ambient temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Substrate temperature should be minimum 5°C/41°F and maximum 35°C/95°F.
Compatibility/Substrates	Suitable for use on GRP and painted surfaces.
Number of Coats	1
Application Methods	Cloth or machine.

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Storage	GENERAL INFORMATION: Exposure to air and extremes of temperature should be avoided. For the full shelf life of Marine Wax to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight. TRANSPORTATION: Marine Wax should be kept in securely closed containers during transport and storage.
Safety	GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line. DISPOSAL: Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Remainders of Marine Wax cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.

IMPORTANT NOTES

The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

Please refer to your local representative or visit <http://www.yachtpaint.com> for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2014.

